


 povrchová úprava / vlastnosti	výška (mm)	rozstup svislých drátů (cm)	Ø drátu horního a dolního (mm)	Ø drátu ostatních (mm)	počet vodor. drátů	váha cca (kg)	bal. (bm)	jedn.	cena za 1 bm bez DPH (CZK)							
									cena za 1 bm bez DPH (CZK)	cena za 1 bm s DPH (CZK)						
Lesnické pletivo ECONOMY - slabší drát 	1000	15	2,0	1,6	8	15	50	bm	19,08	23,09						
	1200				10	18			21,84	26,43						
	1500				14	24			26,64	32,23						
	1600				14	26			27,00	32,67						
	1600				20	33			34,56	41,82						
	1600				23	35			36,00	43,56						
	1800				15	29			29,40	35,57						
	2000				16	28			31,32	37,90						
	Lesnické pletivo EXCLUSIVE - silnější drát 				1000	15			2,5	2,0	8	23	50	bm	24,96	30,20
					1200						10	28			28,92	34,99
1500		14	38	36,12	43,71											
1600		14	41	36,96	44,72											
1600		20	51	47,64	57,64											
1600		23	54	49,68	60,11											
1800		15	46	38,88	47,04											
2000		16	43	43,92	53,14											

Svařované pletivo BENITA	pozinkované (Zn)	1200 1500 1800	6,25	1,8	11 14 18	30 38 47	50	bm	49,44 56,40 72,36	59,82 68,24 87,56
---------------------------------	------------------	----------------------	------	-----	----------------	----------------	----	----	-------------------------	-------------------------

Skoby lesnické Zn	Zn (250 ks/1kg)	délka 31 mm, průměr drátu 3,1 mm	1	1	kg	82,32	99,61
--------------------------	-----------------	----------------------------------	---	---	----	-------	-------

Sloupky UNI tvarované (Zn) 50x30 mm 	ocelový plech s povrř. úpravou Magnelis ©	1300	počet háčků na sloupku: síla stěny sloupku: 1,5 mm	11 háč.	1,6	1	ks	154,80	187,31
		1600		2,0	176,40			213,44	
		1900		2,4	201,60			243,94	
		2200		2,8	225,00			272,25	
Zatloukač sloupků	slouží k pohodlnému zatloukání sloupků 50x30 mm			2,5				1 185,60	1 434,58

LESNICKÉ PLETIVO - role po 50 m
 ECONOMY: Zn - ø drátu 1,6/2,0 mm
 EXCLUSIVE: Zn - ø drátu 2,0/2,5 mm

